# A Graphical Front End for the WIYN Telescope Engineering Data System

Jeffrey W. Percival

*Space Astronomy Laboratory, 1150 University Avenue, Madison, WI 53706 USA*

**Abstract.** The WIYN 3.5m Telescope Control System features a platform independent, network transparent protocol for distributing telescope control data to both local and remote sites. This Engineering Data Subsystem (EDS) can be run in both a burst mode, providing a short (10 s) sampling of 5-axis servo data at the full 200 Hz bandwidth of the system, and a slower (1 Hz) archive mode, which is used to monitor and record control system data during a whole operating session.

The EDS provides over 200 telescope monitors of use to astronomers, engineers, and system designers including pointing performance data, servo and mechanical data, and software state data. The general popularity of this data resource called for a easy way for casual users and experts alike to select data files and particular telescope monitors, graph time-series data, and do simple data manipulations such as pan, zoom, differentiation, and Fourier Transforms. In addition, the inherently distributed nature of the EDS called for a solution that was portable across platforms and operating systems that were in common use by any of the WIYN consortium members.

We have developed a simple but powerful Graphical User Interface to satisfy these needs. It uses the Tk graphical toolkit language and common Unix tools such as shell scripts, grep, and awk to achieve a lightweight but effective solution to the problem of accessing the EDS. The data selection portion of the interface is separate from the graphical manipulation part, which allows both standalone use of the graphing widget in other applications as well as using it with different data selection front ends designed for other telescope systems and scientific instruments.

## 1. Summary of the WIYN Engineering Data Subsystem

The WIYN Engineering Data Subsystem (EDS) is a spacecraft-style telemetry system that sends telescope telemetry (encoders, currents, voltages, pointing data, etc.) in a machine-independent format to clients connected across a network. It has these features:

- It is content-programmable. The data are arranged into Engineering Data Records (EDRs) according to data type. e.g. azimuth servo data share a record, secondary mirror data share a record, etc). Any combination of EDRs can be turned off.

- It is rate-programmable. Each EDR can be programmed to appear at a certain rate, e.g. pointing data once per second, temperatures once per minute, etc).
- A 10-second, 20 Hz "burst mode" can capture all pointing data in the outer pointing loop.
- A 10-second, 200 Hz "burst mode" can capture all servo data in the inner pointing loop.
- All-night telemetry archives contain every command and error message that passed through the system, and once-per-second sampling of over 200 telescope telemetry monitors.

The various data file types (2 burst modes, plus archive mode) and large number of telemetry monitors, not all of which are in each file type, required a tool to lead engineers and scientists through the dazzling array of choices and zero in on what they wanted to see. The design requirements were:

- Lightweight. No budget, need now.
- Portable. Must run on Sun, DECstations, Vaxen.
- Flexible. Rapid prototyping, quick changes.

We chose **Tk** by John Ousterhout at UCB for the overall GUI capability and **blt_graph** by George Howlett at AT&T for the graphing widget. For maximum flexibility, we broke up the problem into two parts:

- The *chooser*, which helps the user select a file type, file name, data type, and data name.
- The *grapher*, with which the user plots, pans, zooms, and prints data. The grapher is a separate program, which allows it to be used apart from the chooser, i.e. as a stand-alone department utility.

## 2. Off the shelf construction

**Tk** and **tcl** are ideal for this sort of low-effort, high-impact tool. We already had differentiators and FFT programs laying about that accepted **graph(1)**-like ASCII input, and a graphical scripting language living close to the Unix shell allowed a quick, painless integration of these existing tools into readily available free-ware. The *chooser* uses simple filename globbing to fill the listbox, and uses **grep(1)** and **awk(1)** to cut and paste the ASCII data file. The *grapher* uses standard **tcl** string operations to test for two-column (suffix .xy) data or one-column (suffix .y) data, with an optional .Z denoting compression.

## 3. tkeds: file name and telemetry chooser

**tkeds** helps the user choose a telemetry file and a specific telemetry monitor to examine.

The left panel presents the three file types: 20 Hz burst file, 200 Hz burst file, and all-night archive. The left-hand listbox shows all choices for the selected file type. The listbox changes when the file type changes.

The right panel presents the major data classifications: telescope axes, mount control electronics, Optical Support Structure, Instrument Adapter Subsystem, and miscellaneous data. The right-hand listbox shows the specific telemetry monitors available for the chosen data type. The listbox changes when the data type changes.

The "plot" button produces a simple ASCII data file, one coordinate pair per line, and then launches the graphing application.





Figure 1. The chooser. This application lets the user select a data file and telemetry monitor, and then launches a graphing application for data display and processing.

## 4. tkgraph: data graphing application

**tkgraph** is the graphing application.

Its primary input data format is like the Unix **graph(1)** program: simple ASCII files, one coordinate pair per line. It also can read ASCII files with one value per line, assuming a simple sequential abscissa. Finally, compressed versions of each of these file types are allowed.

Plot styles include unconnected points, connected points, and a histogram-style plot, emphasizing the sampled nature of the data.

Data processing includes pan and zoom, differentiation, and Fast Fourier Transform.

Output options include postscript disk files and line printer spooling.





Figure 2. The grapher. This application supports panning and zooming, as well as differentiation and Fourier transformation. The data set shown here represents the elevation servo error (85 counts = 1 arcsecond) during a disturbance test in which a 20-lb weight was suspended then cut from the telescope during tracking.





Figure 3. This figure shows a zoomed detail of the Fourier Transform of the data in Fig 2. Structure resonances are clearly displayed for the servo and mechanical engineers.